

Product data sheet for uvex u-chem 3200 cut D



The uvex u-chem 3200 cut D offers a secure grip for handling oil, cooling lubricants and chemicals. The new design stretches and moves easily with the hand giving high levels of dexterity. It also offers excellent chemical protection and resistance to oils and grease.

Suitability for industrial work environments

- Suitable for wet and oily work environments

Material number 60636

7 - 11

Standard EN 420:2003 + A1:2009,
EN 388:2016, EN ISO 374-1:2016,
EN ISO 374-5:2016

Test chemicals n-Heptane (J), Sodium hydroxide 40% (K), Sulphuric acid 96% (L), Nitric acid 65% (M), Ammonia water 25% (O), Formaldehyde 37% (T)

Performance class in accordance with EN 388 4 X 4 1 D

Outer shoe material Polyamide, Polyester (PES), Steel

Coating Nitrile rubber (NBR)

Coating surface area Fully coated

Coating thickness 0.50 mm

Type With gauntlet


Colour Blue, Black, Petrol

EN ISO 374-1:2016 / Type A



J K L M O T

EN 388:2016



4 X 4 1 D

EN ISO 374-5:2016



Manufacturer address

UVEX SAFETY Gloves GmbH & Co. KG
Elso-Klöver-Str. 6
D-21337 Lüneburg
uvex-safety.de