

Product data sheet for uvex rubiflex ESD NB35A



This very light and flexible chemical protection glove is the perfect choice when high electrostatic discharge properties are required in addition to chemical protection and excellent comfort. The uvex rubiflex ESD meets the current standard DIN EN 16350:2014 and has a contact resistance of less than 10^8 ohms. This makes the uvex rubiflex ESD ideal for use in both potentially explosive atmospheres and ESD areas.

Characteristics

- Ergonomic fit
- Good grip
- Very good tactile feel
- For use with touchscreens

Material number 60954

6 - 11

Standard EN 420:2003 + A1:2009,
EN 388:2016

Test chemicals n-Heptane (J), Sodium hydroxide 40% (K), Sulphuric acid 96% (L), Ammonia water 25% (O), Hydrogen peroxide 30% (P), Formaldehyde 37% (T)

Performance class in accordance with EN 388 2 1 1 1 X

Outer shoe material Cotton interlock, Carbon

Coating Nitrile rubber (NBR)

Coating surface area Fully coated

Coating thickness 0.40 mm

Type With gauntlet


Colour Black

EN 388:2016



2 1 1 1 X

EN 388:2016 + A1:2018



2 1 1 1 X



MADE IN GERMANY

Manufacturer address

UVEX SAFETY Gloves GmbH & Co. KG
Elso-Klöver-Str. 6
D-21337 Lüneburg
uvex-safety.de