

Product datasheet

uvex 1 x-tended support BOA® 6567 1-3

Safety shoe DIN EN ISO 20345:2022+A1:2024 S3L FO SC SR Sizes: 35 - 52 | Width: 10, 11, 12











AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (SR)
- oil- and fuel resistant (FO)
- free of silicones, plasticisers and other substances that interfere with wetting agents





FEATURES	
Upper material	breathable microvelour (clima zone)
	water-repellent (WPA)
	suitable for people allergic to chrome
Lining material	textile distance mesh lining for comfortable foot climate
Fastening	BOA® Fit System
heel basket	foamed heel basket for additional stability in the shoe
Comfort	soft padding on collar
	sizes 35-40 have been produced using a women's last
	dust tongue
Innersole	removable comfortable innersole
PROTECTIVE FEATUR	RES
Toe cap	metal-free protective toe cap
Penetration resistance	metal-free, textile penetration resistance
Scuffcap	out of PU for additional protection of the upper material
	(SC)
CERTIFICATES	
uvex medicare+	certified for orthopaedic innersoles and shoe
	adjustments according to the description in DGUV 112-
	191
100% vegan	certified free from animal ingredients and products difficulty products and products
	additional protection for people with allergies and intolerances
ESD	protection against electrostatic charge according to EN
200	61340-4-3 und EN 61340-5-1
SUSTAINABILITY	
Recycled/sustainable materials	removable innersole and lacing system made wholly or
	partly from recycled materials
	free from harmful substances in accordance with the
	uvex restricted substances list
ACCESORIES/ SPARE	PARTS
Replacement innersole	• 9534 7-0
BOA® Replacement kit	• 6564000
Semi-orthopaedic	tune-up SECOSOL® COMPLETE+
innersoles	• low: 95281 • low: 94790
	medium: 95282 medium: 94791