

Product datasheet

uvex 1 x-craft pro D30® 6806 1-3

Safety shoe DIN EN ISO 20345:2022+A1:2024 S1 PS FO M SC SR

Sizes: 35 - 52 | Width: 10, 11, 12



AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Dual-density polyurethane sole



- shock-absorbing and energy-returning uvex i-PUREnri planet midsole with 15 % recycled granulate from residues
- **bionom** x – ergonomically designed PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES

Upper material	• durable and flexible PUtek upper material in the forefoot area • breathable, lightweight and tear-resistant ripstop upper material • suitable for people allergic to chrome • textile distance mesh lining for comfortable foot climate • elastic laces • foamed heel basket out of PU for additional stability in the shoe • for increased visibility even in dark working environments • soft padding on collar • sizes 35-40 have been produced using a women's last • perforated tongue foam for increased breathability (clima zone) • removable comfortable innersole
Lining material	
Fastening	
Heel basket	
Reflecting elements	
Comfort	
Innersole	

PROTECTIVE FEATURES

Toe cap	• metal-free protective toe cap
Anti-penetration	• metal-free, textile penetration resistance (tested with 3 mm test nail)
Scuffcap	• out of PU for additional protection of the upper material (SC)
Metatarsal protection	• certified D3O® metatarsal protection up to 100 J (M)

CERTIFICATES

uvex medicare+	• certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112-191 • certified free from animal ingredients and products • additional protection for people with allergies and intolerances • protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1
100% vegan	
ESD	

SUSTAINABILITY

CO ₂ footprint	• 8.71 kg Cradle-to-Customer (calculation date 10/2025)
Recycled/sustainable materials	• midsole, penetration resistance and removable innersole made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list

ACCESORIES/ SPARE PARTS

Replacement innersole	• 9579 7-0 • low 95284 • medium 95285 • high 95286
tune-up innersole	• black 8446020 • 9591300
Laces	
Elastic laces	