

Product data sheet uvex silv-Air 7100 FFP1 NR D



Product information

Product features	<ul style="list-style-type: none">• Particle-filtering cup shape mask without valve• Protection level FFP 1• Soft material edges for increased comfort• Seamless, continuous headband for a comfortable, secure fit• Manufactured without plastic or metal parts• Compatible with safety eyewear thanks to an optimized design in the nose area (indentations on the left and right-hand side of the nose)• Mask fulfils the requirements of the dolomite dust test (D)
Materials	Headband: synthetic latex Filter/mask: PP, Polyester
Weight	12 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8707.100	cup shape mask FFP1, grey without valve	20 pcs. per box

Packaging sizes

Box	approx. 135 x 135 x 285 mm
Outer Carton	approx. 410 x 410 x 310 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 4 times the respective limit values.	Particles (neither toxic nor associated with fibrosis), Agriculture, hay, food industry, grain, flour, graphite, chalk, marble, rust.
---	---

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.