

Product data sheet uvex silv-Air 7310 FFP3 R D



Product information

Product features	<ul style="list-style-type: none">• Particle-filtering cup shape mask with exhalation valve• Protection level FFP 3• Soft material edges for increased comfort• Soft sealing lip guarantees a secure, comfortable sealed position of the mask• Integrated, flexible, adjustable nose clip• 4-point headband attachment allows an individual and secure fit• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask• Mask fulfils the requirements of reusability (R) and the dolomite dust test (D)
Materials	Headband: textile Headband clips: Polypropylene Nose clip: metal, PP Filter/mask: PP, Polyester Sealing lip: synthetic foam Valve: PP
Weight	25 g
Standard	EN 149:2001 + A1:2009

Versions & Accessories

Article number	Colour/Version	Retail unit
8707.310	cup shape mask FFP3, grey with valve	5 pcs. per box
8701.011	uvex clear cleaning spray	1 can, 360ml

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values.	Woodworking, hard wood, chromium, asbestos (up to 100,000 F/m ²), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.
--	--

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.