

Breathing Protection

01.03.2021

Product data sheet uvex silv-Air 7320 FFP3 R D with Carbon



Product information

Product features	 Protection let Soft material Soft sealing I position of th Integrated, fle 4-point headle fit Exhalation value Activated car value 	 Soft material edges for increased comfort Soft sealing lip guarantees a secure, comfortable sealed position of the mask Integrated, flexible, adjustable nose clip 4-point headband attachment allows an individual and secure fit Exhalation value reduces breathing resistance and build-up of heat moisture in the mask Activated carbon filter for odors, gases and vapors below limit value Mask fulfils the requirements of reusability (R) and the 	
Materials	Headband: Headband clips: Sealing lip: Nose clip: Filter/mask: Valve:	textile Polypropylene synthetic foam metal, PP PP, Polyester PP	
Weight	27 g		
Standard	EN 149:2001 + A1:20	009	

Versions & Accessories

Article number	Colour/Version	Retail unit
8707.320	cup shape mask FFP1, silver-grey with valve and carbon	5 pcs. per box
	and carbon	
8701.011	uvex clear cleaning spray	1 can, 360ml

Packaging sizes

Box	approx. 140 x 182 x 190 mm	
Outer Carton	approx. 610 x 410 x 370 mm	

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance	Inhalation resistance	Exhalation resistance
	30I/min.	95l/min.	160I/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the	Woodworking, hard wood, chromium, asbestos (short periods of work), stainless steel, lead, welding, dust that contain	
respective limit values.	beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.	

^{*}Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth