

Product data sheet uvex silv-Air 8213 FFP2 NR D



Product information

Product features	<ul style="list-style-type: none"> • Particle-filtering flat fold mask with exhalation valve • Protection level FFP 2 • Soft material edges for increased comfort • Seamless, continuous headband for a comfortable, secure fit • Integrated, flexible, adjustable nose clip • Hydrophobic coating • Foam pads at chin and nose area offers a perfect fit • Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask • The masks are individually packed • Mask fulfils the requirements of the dolomite dust test (D) 										
Materials	<table> <tr> <td>Headband:</td> <td>synthetic latex</td> </tr> <tr> <td>Nose clip:</td> <td>metal, PP</td> </tr> <tr> <td>Sealing lip:</td> <td>synthetic foam</td> </tr> <tr> <td>Filter/mask:</td> <td>PP, Polyester</td> </tr> <tr> <td>Valve:</td> <td>PP</td> </tr> </table>	Headband:	synthetic latex	Nose clip:	metal, PP	Sealing lip:	synthetic foam	Filter/mask:	PP, Polyester	Valve:	PP
Headband:	synthetic latex										
Nose clip:	metal, PP										
Sealing lip:	synthetic foam										
Filter/mask:	PP, Polyester										
Valve:	PP										
Weight	15 g										
Standard	EN 149:2001 + A1:2009										

Versions

Article number	Colour/Version	Retail unit
8708.213	Flat fold mask FFP2, silver with valve	15 pcs. per box

Packaging sizes

Box	approx. 155 x 160 x 160 mm
Outer Carton	approx. 610 x 505 x 340 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 10 times the respective limit values.	Woodworking, softwood, cement, metal, smog, fine dust, concrete, iron dust, ash, cotton dust, fluoride, carbon fibres, gypsum, fibre glass, copper, nickel, soot, pollen, house dust, pet hair.
--	---

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth