

Product data sheet uvex silv-Air 3100 FFP1 NR D



Product information

Product features	<ul style="list-style-type: none">• Particle-filtering flat fold mask without valve• Protection level FFP1• Soft material edges for high wearing comfort• Continuous head band for a comfortable and secure fit• Flexible and adjustable nose clip• Soft sealing lip guarantees a secure, comfortable sealed position of the mask• The masks are individually packed• Compatible with uvex safety eyewear• Mask fulfils the requirements of the dolomite dust test (D)
Materials	Headband: textile Nose clip: PP Headband clips: PP Filter/mask: Melt Blown PP, Polyester Sealing lip: EVA foam
Weight	10 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8733.100	Flat fold mask FFP1, white without valve	30 pcs. per box
8753.100	Flat fold mask FFP1, white without valve	3 pcs. per bag

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 4 times the respective limit values.	Particles (neither toxic nor associated with fibrosis), Agriculture, hay, food industry, grain, flour, graphite, chalk, marble, rust.
---	---

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advice.