

Breathing Protection

02.03.2021

Product data sheet uvex silv-Air 3100 FFP1 NR D





Product information

Product features	 Particle-filtering flat fold mask without valve Protection level FFP1 Soft material edges for high wearing comfort Continuous head band for a comfortable and secure fit Flexible and adjustable nose clip Soft sealing lip guarantees a secure, comfortable sealed position of the mask 			
	 The masks are individually packed Compatible with uvex safety eyewear Mask fulfils the requirements of the dolomite dust test (D) 			
Materials	Headband: textile Nose clip: PP Headband clips: PP Filter/mask: Melt Blown PP, Polyester Sealing lip: EVA foam			
Weight	10 g			
Standard	EN 149:2001 + A1:2009			

Versions

Article number	Colour/Version	Retail unit
8763100	Flat fold mask FFP1, white without valve	30 pcs. per box
8743100	Flat fold mask FFP1, white without valve	3 pcs. per bag

Packaging sizes

Box	approx. 210 x 140 x 125 mm
Outer Carton	approx. 540 x 430 x 230 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance	Inhalation resistance	Exhalation resistance
	30I/min.	95I/min.	160I/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be	Particles (neither toxic nor associated with
used against solid, aqueous and non-	fibrosis), Agriculture, hay, food industry,
volatile liquid aerosols up to 4 times the	grain, flour, graphite, chalk, marble, rust.
respective limit values.	

^{*}Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.