

Product data sheet for uvex rubiflex NB27S



For these chemical protection gloves, a thicker cotton interlock lining is used. This makes the uvex rubiflex S suitable for many applications in which protection against chemicals and increased mechanical protection (for example against heat) is required. The special 60 or 80 cm version is also available with elasticated gauntlet end.

Characteristics

- Ergonomic fit
- Good grip
- Very good tactile feel

Material number 89646

7 - 11

Standard

EN 420:2003 + A1:2009,
EN 388:2016, EN ISO 374-1:2016

Test chemicals

n-Heptane (J), Sodium hydroxide 40% (K), Acetic acid 99% (N), Ammonia water 25% (O), Hydrogen peroxide 30% (P), Formaldehyde 37% (T)

Performance class in accordance with EN 388 2 1 2 1 X

Outer shoe material Cotton interlock

Coating Nitrile rubber (NBR)

Coating surface area Fully coated

Coating thickness 0.50 mm

Type With gauntlet

Colour Green

Glove length 27 cm

EN ISO 374-1:2016 / Type A



JKNOPT

EN 388:2016



2 1 2 1 X



MADE IN GERMANY

Manufacturer address

UVEX SAFETY Gloves GmbH & Co. KG
Elso-Klöver-Str. 6
D-21337 Lüneburg
uvex-safety.de