

Product Datasheet model uvex pheos cx2 9198 014

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

1. Product Characteristics

- sporty looking safety spectacle with high wearer acceptance
- x-tended eyeshield: soft seal frame technology wraps around the brow providing protection from particle ingress
- ergonomically shaped side arms with soft-grip temple ends provide a comfortable, secure fit without pressure
- soft, flexible nose pad adapts to the wearer, delivering a non-slip and pressure-free fit
- robust polycarbonate lens with uvex's proven supravision coating technology – permanent anti-fog and scratch-resistant lens
- UV400 – 100% protection against dangerous UV radiation up to 400 nm
- metal-free

2. Technical Details Body

Side arms

Material	POM / TPE
Colour	silver, black

Marking

Manufacturer 's ID code	W
Applicable EN norm	166
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperature	T
Conformity symbol	CE

3. Technical Details Lens




Material	PC
Thickness	2.2 mm at PD
Coating	uvex supravision excellence
Colour	clear
UV protection	UV400

Marking

Filter	5-2.5 (EN 172)
Manufacturer 's ID code	W
Optical class	1
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperature	T
Scratch resistance	K
Antifog	N
Conformity symbol	CE
Factory symbol	

4. Logistical Information

Product

Weight	28g		
Dimensions (L x W x B) in approx. mm	 picture only for reference		
	160 x 142 x 48		
	Packing unit 1	Packing unit 2	Packing unit 3
EAN Code	4066853017240	4066853017257	4066853017264
Quantity in pcs.	1	10	160
Dimensions (L x W x H) in approx. mm	 picture only for reference		
	55 x 150 x 60	185 x 290 x 97	600 x 400 x 400
Net weight in approx. g	28	280	4,480
Gross weight in approx. g	42	525	9,270
Country of Origin	Germany		

5. Miscellaneous

Standards	EN 166 + EN 172
PPE Category	Category II