

Product datasheet

uvex 2 xenova® 9555 7-9

Safety shoe DIN EN ISO 20345:2022 S2 FO SR

Sizes: 35 - 52 | Width: 10, 11, 12











AREA OF APPLICATION

Medium applications usually alternate between indoor and outdoor areas, meaning that the demands on the robustness of the outsole of a safety shoe are much higher.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole with 15% recycled granulate from residues
- antistatic
- short-term heat resistant up to 120°C
- excellent slip resistance (SR)
- oil- and fuel resistant (FO)
- free of silicones, plasticisers and other substances that interfere with wetting agents





FEATURES	
Upper material	hydrophobic leather
	water-repellent (WPA)
Lining material	 textile distance mesh lining for comfortable foot climate (clima zone)
Fastening	• laces
Reflecting elements	for increased visibility even in dark working environments
Comfort	soft padding on collar
	sizes 35-40 have been produced using a women's lastdust tongue
Innersole	removable comfortable innersole
Furthermore	metal-free
PROTECTIVE FEATUR	RES
Toe cap	metal-free protective toe cap
CERTIFICATES	
uvex medicare+	 certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112- 191
ESD	 protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1
SUSTAINABILITY	
Recycled/sustainable materials	midsole, removable innersole, insole board and heel cap
	made wholly or partly from recycled materials
	free from harmful substances in accordance with the
ACCECODIEC/CDADE	uvex restricted substances list
ACCESORIES/ SPARE	
Replacement innersole	• 9534 7-0
tune-up innersole	• low 95281
	• medium 95282
Laces	high 95283black 9599921
Luoco	■ DIAUN JUJJJLI